



Classic Tool Design, Inc.

31 Walnut Street

New Windsor, NY 12253

800-562-7420 | 845-562-8700 | www.CTD4ac.com | Info@Ctd4ac.com

MSDS SHEET for CLASSIC PRO A/C FLUSH

1) COMPONENT INFORMATION

Chemical	CAS Reg. No.	Percentage (%)
Proprietary	Proprietary	Proprietary

2) PORT HEALTH EFFECTS FROM OVER EXPOSURE

Eye:	May cause moderate to high irritation.
Inhalation:	If sprayed or misted may cause chemical pneumonia. Inhalation can cause nose, throat and respiratory tract irritation.
Ingestion:	Product is harmful if swallowed. Ingestion may cause vomiting, headache and other medical problems.
Skin:	May be irritating. Skin contact may cause slight redness. Contains a potential skin sensitizer.

Medical conditions generally aggravated by exposure: Persons with allergies or pre-existing conditions should avoid contact with this product.

3) FIRST AID PROCEDURES

Eye:	Remove contact lens at once. Flush with water for at least 15 minutes. If irritation persists seek medical attention.
Skin:	Remove contaminated clothing-Launder or dry clean clothes before reuse. Dispose of leather articles. Wash affected area with copious amounts of soap and water. If irritation develops seek medical attention.
Inhalation:	Evacuate to a safe area with plenty of fresh air. Apply cardiopulmonary resuscitation if required. Administer oxygen if available. If resuscitation required seek medical aid immediately. Allow victim to rest in a well ventilated area ten seek medical aid immediately.
Ingestion:	DO NOT induce vomiting. Seek medical attention immediately.

5) FIRE FIGHTING PROCEDURES

Flammable Limits:	LEL 0.7% UEL 6.01%
Unusual Hazards:	Smoke may be acrid and fumes irritating. Burning generates CO, CO ₂ and smoke. Combustible Liquid. Guard against spontaneous combustion of improperly discarded oily rags.
Extinguishing Agents:	Dry chemical, CO ₂ or foam.
Protective Clothing:	Fire-fighters should use NIOSH/MNSA approved self-contained breathing apparatus and full protective gear.
Fire-fighting Procedures:	Use water fog to cool fire exposed containers. USE WATER CAREFULLY NEAR EXPOSED/BURNING LIQUIDS. May cause frothing and splashing of hot material. Handle as oil fire.

6) SPILL OR LEAK HANDLING PROCEDURES

Personal Protection:	Wear Protective clothing including splash proof goggles, rubber gloves and rubber overshoes. Remove all contaminated clothing promptly.
Procedures:	Floor may be slippery, use care to avoid falling. Contain spill immediately with inert material (e.g. sand, earth). Transfer liquids and solid diking material to separate suitable containers for recovery or disposal. Do not hose down drain or sewers. CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

7) HANDLING AND STORAGE

Avoid contact with eyes, skin and clothing.

Usual precaution for combustible liquids.

Ensure that containers are properly secured before moving.

Keep container closed and keep away from oxidizing materials.

Store in cool-well ventilated sprinkler warehouse.

Store in tightly sealed bulk containers below 70°F. Partially filled containers should be blanketed with nitrogen.

Product may expand slightly in storage causing pressure to build in container. Open container carefully if product appears to be under pressure.

Avoid temperatures over 115°F.

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. For work on tanks refer to Occupational Safety and Health Administration regulations, ANSI Z49.1, and other governmental and industrial references pertaining to cleaning, repairing, welding, or other contemplated operations.